

# Extreme Metal in a Compact Pedal

With its extreme gain, the ML-2 is the most potent and heavy distortion pedal ever created by BOSS. It easily delivers massive distortion and gain with heavy lows for playing Nu Metal, Grind Core, Industrial, Hard Core, or any genre that requires crushing sound. The ML-2's ferocious and biting tone will complement and cut through any blast beats your rhythm section can create.



- Ultra-heavy distortion with sharp-edged attack for crushing metal riffs
- LOW control for heavy, low frequency sound a la 7-string guitar or dropped tuning
- HIGH control for screaming, metallic tone
- Road-tough BOSS metal construction

\*Actual product appearance may be subject to change.

### ML-2 Specifications

■ **Nominal Input Level** -20 dBu ■ **Input Impedance** 1 M $\Omega$  ■ **Nominal Output Level** -20 dBu ■ **Output Impedance** 1 k $\Omega$  ■ **Recommended Load Impedance** 10 k $\Omega$  or greater ■ **Controls** Pedal Switch, LEVEL Knob, LOW Knob, HIGH Knob, DIST Knob ■ **Indicator** CHECK Indicator (Serves also as battery check indicator) ■ **Connectors** INPUT Jack, OUTPUT Jack, AC adaptor Jack ■ **Power Supply** DC 9 V: Dry battery 6F22 (9 V) type (carbon), Dry battery 6LR61 (9 V) type (alkaline), AC Adaptor (PSA series: optional) ■ **Current Draw** 36 mA (DC 9 V) ■ **Expected battery life under continuous use** Carbon: 3 hours, Alkaline: 10 hours ■ **Dimensions** 73 (W) x 129 (D) x 59 (H) mm, 2-7/8 (W) x 5-1/8 (D) x 2-3/8 (H) inches ■ **Weight**

440 g/ 1 lb (including battery) ■ **Accessories** Owner's Manual, Leaflets (USING THE UNIT SAFELY, IMPORTANT NOTES, and Information), Dry Battery 006P/9V (6LR61) ■ **Options** AC Adaptor (PSA series)

\* The battery that was supplied with the unit is for temporary use - intended primarily for testing its operation.  
\* We recommend that alkaline battery be used when replacing the battery.

\* 0 dBu=0.775 Vrms

\* The specifications are subject to change without notice.